

AD-A253 909

SECURITY CLAS



REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-01881a. REPORT SECURITY CLASSIFICATION
UNCLASSIFIED

1b. RESTRICTIVE MARKINGS

2a. SECURITY CLASSIFICATION AUTHORITY 1992

3. DISTRIBUTION / AVAILABILITY OF REPORT

2b. DECLASSIFICATION / DOWNGRADING SCHEDULE

UNLIMITED

This document has been approved
for public release and sale; its
distribution is unlimited.

4. PERFORMING ORGANIZATION REPORT NUMBER(S)

5. MONITORING ORGANIZATION REPORT NUMBER(S)

DOD POP HMTR/AYD 91-021

6a. NAME OF PERFORMING ORGANIZATION

6b. OFFICE SYMBOL
(If applicable)

7a. NAME OF MONITORING ORGANIZATION

PACKAGING DIVISION, AED

SMCAR-AEP

6c. ADDRESS (City, State, and ZIP Code)

U.S. ARMY, ARDEC
PICATINNY ARSENAL, NJ 07806-5000

7b. ADDRESS (City, State, and ZIP Code)

8a. NAME OF FUNDING / SPONSORING
ORGANIZATION8b. OFFICE SYMBOL
(If applicable)

9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER

N/A

8c. ADDRESS (City, State, and ZIP Code)

10. SOURCE OF FUNDING NUMBERS

PROGRAM
ELEMENT NO.PROJECT
NO.TASK
NO.WORK UNIT
ACCESSION NO.

11. TITLE (Include Security Classification)

PERFORMANCE ORIENTED PACKAGING REPORT FOR THE FIRING DEVICE, DEMOLITION, TIME DELAY, XM147

12. PERSONAL AUTHOR(S)

DZURY, R. CHRIS

13a. TYPE OF REPORT

FINAL

13b. TIME COVERED

FROM _____ TO _____

14. DATE OF REPORT (Year, Month, Day)

91-12-30

15. PAGE COUNT

16. SUPPLEMENTARY NOTATION

SEE ATTACHED

17. COSATI CODES

FIELD GROUP SUB-GROUP

18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)

19. ABSTRACT (Continue on reverse if necessary and identify by block number)

THIS REPORT CONTAINS THE TESTS PERFORMED AND TEST RESULTS ON THE FIRING DEVICE,
DEMOLITION, TIME DELAY, XM147, PACKED 24 PER PA19 METAL AMMUNITION CONTAINER, TWO
PA19's PER WIREBOUND BOX FOR PERFORMANCE ORIENTED PACKAGING CERTIFICATION.

92 8 12 015

92-22764

20. DISTRIBUTION / AVAILABILITY OF ABSTRACT

☒ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT ☐ DTIC USERS

21. ABSTRACT SECURITY CLASSIFICATION

UNCLASSIFIED

22a. NAME OF RESPONSIBLE INDIVIDUAL

STEVE RUFFINI

22b. TELEPHONE (Include Area Code)

201-724-2515

22c. OFFICE SYMBOL

SMCAR-AEP

1. DATA SHEET:

Container:

Type: Box, Wood, Wirebound

UN Code: 4C1

Specification Number: PPP-B-46506

Material: wood and wire

Capacity: 1167.9 cubic inches

Drawing Number: 9366708

Dimensions: I.D. (in.): 12 1/2 X 12 1/6 X 10 3/8

Tolerance: +1/8

O.D. (reference, in.): 14 7/8 X 12 13/16 X 11 15/16

Closure (method/Type): bent wire

Tare Weight: 7 lbs.

Packed Out Container Weight (48 Firing Devices): 52 lbs.

Product:

Name: Firing Device, Demolition, Time Delay, XM147

NSN: 1375-01-340-7890

Drawing Number: 12914600

Proper Shipping Name: Fuzes, Detonating

Identification Number: UN 0257

Physical State: Solid

Quantity Per Wirebound Wood Box: 48

BACKGROUND AND TESTING:

This report contains the tests performed and test results of the Firing Device, Demolition, Time Delay, XM147 packed (24) twenty-four per PA19 metal ammunition container, (2) PA19's per wirebound box in accordance with drawing 12913801 for Performance Oriented Packaging Certification. Instead of testing this container configuration with the weight listed above, each PA19 container was loaded with steel weights weighing 34 lbs. and fiberboard filler. The final packed out weight of each wirebound box tested was 94 lbs. This is an acceptable analogy in accordance with Code of Federal Regulations Title 49. The following tests were performed in accordance with Performance Oriented Packaging test regulations of Code of Federal Regulations Title 49:

a. Stacking Test: Three wirebound wood boxes, each containing 2 PA 19 containers, were placed next to each other in a compression tester under a total load of 3800 lbs. for 64 hours. This exceeds the CFR requirement which is a load these wirebound boxes would see when at the bottom of a stack of wirebound boxes measuring 10 feet high for a period of 24 hours.

b. Loose Cargo Test: The loaded wirebound boxes which underwent the stacking test were then loose cargo tested together for one hour on a table having a steel plate and restraining walls. The rpms of the machine were adjusted so a 1/16 inch thick piece of material could be moved freely between the container and the steel plate. The test duration and machine input were in accordance with the CFR requirement.

c. Drop Test: After the three wirebound boxes were loose cargo tested, they were drop tested from 4 feet onto a steel plate in the following orientations:

<u>container</u>	<u>orientations dropped</u>
1	flat on top flat on bottom
2	flat on a long side flat on a short side
3	directly on a corner

These orientations are in accordance with the CFR requirement for a rectangular box.

3. TEST RESULTS: After each test, both PA19 containers remained consolidated in each wirebound box and there was no spillage or leakage of contents from any PA19 container. This is the criteria for successfully passing Performance Oriented Packaging Testing as prescribed in CFR Title 49. Therefore, this container configuration is considered safe for international shipment and in accordance with Performance Oriented Packaging Regulations.

DTIC QUALITY INSPECTED 5

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	